



Gaztek Slim X-Ray Premium LED Illuminator View Panel



Uniform Clear Vision

Best Luminous Efficacy

- Design, Assembly & Manufacturing all Make In India
- Automatic Film Activation & Film Holding
- LED Heat Dissipation Technology For Extended Life
- Corrosion Proof Coated Push-Fit Back Cover



Model	Viewing Area LxH (cm)	Luminous Density (Lux*)	Light Source & Temp	Watts(W) & Lumens(L) for Single Panel	Power Input (Volts)	Outer Dimension LxHxB (cm)
Single Film GXFV 1	36 x 44	7000 - 12000	LED 6500 K	12 W, 6300 L	220 - 240 AC	44 x 52 x 2.5
Two Film GXFV 2	72 x 44	7000 - 12000	LED 6500 K	12 W, 6300 L	220 - 240 AC	82 x 52 x 2.5
Three Film GXFV 3	110 x 44	7000 - 12000	LED 6500 K	12 W, 6300 L	220 - 240 AC	118 x 52 x 2.5
Four Film GXFV 4	145 x 44	7000 - 12000	LED 6500 K	12 W, 6300 L	220 - 240 AC	153 x 52 x 2.5

Product Specifications are subject to change without notice



Gaztek Slim X-Ray Premium LED Illuminator View Panel



- Best in class aesthetically appealing 25mm thickness sleek designed integrated X-Ray View Panel
- Best in class Lifetime warranted Luxurious Aluminium Anodized Brush Finish for easy to wipe clean thereby ensuring Medical hygiene germ free compliance
- Best in class housing frame assembly with protection from ingress of insects ,dust & moisture
- Corrosion proof coated push fit back cover sealing the view panel completely from ingress of moisture during monsoons and wall dampness
- Best in class Life time warranted Non-yellowing Opal Acrylic panel diffuser

-
- The First and only of its kind, aesthetically appealing ABS/PC moulded 4 corners for wall mounting installation as compared to others with suspended / hanging as the only option
 - First of its kind LED High heat dissipation design for extended life upto 100,000 hours
 - Integrated advanced power supply with 10-100% Stepless Low-Voltage Dimming and Automatic film activation & film holding capability
 - The molded power cable with earthing complies with Class I electrical safety standards



-
- The three-way power switch offers MANUAL ON/OFF/AUTOMATIC FILM ACTIVATION modes
 - AC 240V (50Hz) input for medical product safety with external 2A fuse rating to prevent short circuits, fire hazards, and electrical shocks.
 - Made in India. One year manufacturer warranty & additional 4 years service warranty (T&C apply)